

Format hard disk in linux using fdisk

Written by sdx

Wednesday, 15 May 2013 16:25 -

new disk using fdisk command

Following command will list all detected hard disks:

```
# fdisk -l | grep '^Disk'
```

Output:

```
Disk /dev/sda: 251.0 GB, 251000193024 bytes
```

```
Disk /dev/sdb: 251.0 GB, 251000193024 bytes
```

A device name refers to the entire hard disk. For more information see Linux partition naming convention and IDE drive mappings.

To partition the disk - /dev/sdb, enter:

```
# fdisk /dev/sdb
```

The basic fdisk commands you need are:

- * m - print help
- * p - print the partition table
- * n - create a new partition
- * d - delete a partition
- * q - quit without saving changes
- * w - write the new partition table and exit

Step#2 : Format the new disk using mkfs.ext3 command

To format Linux partitions using ext2fs on the new disk:

```
# mkfs.ext3 /dev/sdb1
```

Step#3 : Mount the new disk using mount command

First create a mount point /disk1 and use mount command to mount /dev/sdb1, enter:

```
# mkdir /disk1
```

```
# mount /dev/sdb1 /disk1
```

```
# df -H
```

Step#4 : Update /etc/fstab file

Open /etc/fstab file, enter:

```
# vi /etc/fstab
```

Append as follows:

```
/dev/sdb1          /disk1          ext3  defaults    1 2
```

Save and close the file.

Task: Label the partition

You can label the partition using e2label. For example, if you want to label the new partition

Format hard disk in linux using fdisk

Written by sdx

Wednesday, 15 May 2013 16:25 -

/backup, enter

e2label /dev/sdb1 /backup

You can use label name insted of partition name to mount disk using /etc/fstab:

LABEL=/backup /disk1 ext3 defaults 1 2